



11 Pieces 20-in-1 Interchangeable Screwdriver Set

Features:

- Professional SNCM+V Alloy Steel Blade
- Precision Machined Magnetic Tip
- Double-Ended Reversible Blades
- Quick-Release Blade Retainer
- Anti-Slip Featured Grip



Ergonomic designed handle provides optimum comfort in use especially for high torque tightening and loosening works.



Special blade retainer with quick-release function locks the blade firmly in the place and provides an instant change between different sizes.



ITEM NO.	Satin	GAAI2101
CONTENTS		20 (SET)
1 FMAA0102		
	1/4" Hex Shank Double End Phillips Screwdriver Bits PH1xPH2 - 175mm (L)	
1 FMBA0102		
	1/4" Hex Shank Double End Pozi Screwdriver Bits PZ1xPZ2 - 175mm (L)	
2 FMCA0406 & 0507		
	1/4" Hex Shank Double End Slotted Screwdriver Bits 4x6, 5x7mm - 175mm (L)	
3 FMEA0404-0606		
	1/4" Hex Shank Hex & Ball Point Screwdriver Bits 4x4, 5x5, 6x6mm - 175mm (L)	
3 FMDA1015-3040		
	1/4" Hex Shank Double End Star Screwdriver Bits T10xT15, T20xT25, T30xT40 - 175mm (L)	
1 COAJ0814		
1/4" Hex Shank Screwdriver Handle 1/4" x 136mm (L)		
BLOW CASE: W240 x D170 x H50 (mm)		

1/4" Hex Shank Screwdriver Handle



ITEM NO.	HEX (inch)	L (mm)		
COAJ0814	1/4	136	5	40

1/4" Hex Shank Double End Phillips Screwdriver Bits

(SNCM+V)



TYPE	ITEM NO.	SIZE	L (mm)		
	FMAA0102	PH1xPH2	175	30	240

1/4" Hex Shank Double End Slotted Screwdriver Bits

(SNCM+V)



TYPE	ITEM NO.	SIZE	L (mm)		
	FMCA0406	4x6mm	175	30	240
	FMCA0507	5x7mm	175	30	240

1/4" Hex Shank Double End Pozi Screwdriver Bits

(SNCM+V)



TYPE	ITEM NO.	SIZE	L (mm)		
	FMBA0102	PZ1xPZ2	175	30	240

1/4" Hex Shank Phillips & Slotted Screwdriver Bits

(SNCM+V)



TYPE	ITEM NO.	SIZE	L (mm)		
	FMFA0206	PH2x6mm	175	30	240

1/4" Hex Shank Double End Star Screwdriver Bits

(SNCM+V)



TYPE	ITEM NO.	SIZE	L (mm)		
	FMDA1015	T10xT15	175	30	240
	FMDA2025	T20xT25	175	30	240
	FMDA3040	T30xT40	175	30	240

1/4" Hex Shank Hex & Ball Point Screwdriver Bits

(SNCM+V)



TYPE	ITEM NO.	SIZE	L (mm)		
	FMEA0404	4x4mm	175	30	240
	FMEA0505	5x5mm	175	30	240
	FMEA0606	6x6mm	175	30	240

