### **//** 56PCS

Professional Threaded Coil-Insert Repair Kit (For Spark Plug Thread)



- ☐ Ideal for repairing and restoring damaged spark plug thread
- Completed set for easy and quick repairs of spark plug, thread insert size M10, M12, M14
- Each size includes Stainless Steel Screw Coils,
  Thread Tap & Coil Shielding Collar, Coil Installation
  Shank and Hex Key Wrench

Shank and	u nex key wiench		
ITEM NO.	CONTENTS	10 (SET)	
JGAI5601	45 Stainless Steel Screw Coil Inserts 15PCS - M10 x 1.0mm x 3/8" (L=9.5mm) 15PCS - M12 x 1.25mm x 3/4" (L=19mm) 15PCS - M14 x 1.25mm x 7/16" (L=11mm)		
	3 Thread Taps M10 x 1.0mm, M12 x 1.3 M14 x 1.25mm	25mm,	
	3 Coil Shielding Collar		

- 3 Coil Shielding Collar M10, M12, M14
- 3 Coil Installation Shank M10, M12, M14
- Hex Key Wrench

**BLOW CASE**: W298x D298 x H62 (mm)



 Tap re-drilled hole using tap



 Set-up locking block to adjust coil insert depth



Load coiled insert into Coil Shielding Collar



Screw coil into thread slowly

# Collai

5. Using Pliers, take off pin on insert



6. Thread is repaired and ready to use

# // 10PCS Professiona

Professional Threaded Coil-Insert Repair Kit (For Spark Plug Thread)



- ☐ Ideal for repairing and restoring damaged spark plug thread
- For most commonly used metric bolt size M14, suitable for machine construction, engine repair and other automotive applications

oti ioi aato	mouve applications
ITEM NO.	CONTENTS # 30 (SE
JGAI1003	1 Install Main Tool (P-type)
	1 2mm Hex Key Wrench
	1 HSS Thread Tap M14 x 1.25mm
	1 Coil Shielding Collar M14
	1 Coil Installation Shank M14
	5 Stainless Steel Screw Coil Inserts M14 x 1.25mm x 7/16" (L=11mm)

**BLOW CASE:** W250 x D128 x H41 (mm)

## // 3PCS

3/8" DR. Glow Plug Socket Set

(CR-V)



# // 3/8" DR. Deep Spark Plug Socket

Spark Plug Gap Gauge (Coin Type)





- Rubber insert for positive plug protection and retention
- Professional quality, 12-point deep sockets manufactured from hardened and tempered Chrome Vanadium Steel
- Designed for easy installation or removal of the deep-seated (deeply recessed) spark plugs
- Fitted with a rubber insert for plug protection and retention
- ☐Knurled finger grips for hand starting
- Polished chrome plated

3/8'





- Coin-type ramp gauge design to measure all type spark plug gaps easily
- Flanged hole design to adjust side wire without damaging center electrode
- Dual marked for both Imperial and Metric

ITEM NO.	Measuring Range		曲
JDBU0210	0.020" - 0.100" (0.6 - 2.4mm)	24	288



- ☐6-point socket made of hardened and tempered Chrome Vanadium Steel
- ☐Internal rubber retaining ring for positive retention of plug in socket
- 180° universal joint design allows easy access in confined engine bays
- Suitable for the removal and replacement of glow plugs in most popular diesel engines
- Matt chrome plated finish
  Application: Mercedes-Benz, Audi, VW, Opel, Fiat
- and etc.

JGAI0301 3 JDBM1208~JDBM1212 3/8" Dr. Glow Plug Sockets (75mmL) 8, 10, 12 mm

BLOW CASE: W120 x D81 x H36 (mm)