



Digital Torque / Angle Wrench with Reversible Ratchet Insert Tool

- ☐ Torque accuracy: CW $\pm 2\%$ & CCW $\pm 3\%$ tolerance of the set scale value
- ☐ Angle accuracy: $\pm 2^\circ$ (rotating 90° at speed of $30^\circ/\text{sec}$)
- ☐ Operating mode: Peak hold mode (peak value detection) / Track mode (continuous display)
- ☐ Unit selection: Nm, Ft-Lb, In-Lb, Kg-cm and Degree
- ☐ Rotation angle range: Up to 999°
- ☐ Storage memory: 50 Readings
- ☐ 12 way lights and buzzer when torque value is reached
- ☐ Low battery indicator and auto shut off (after 2 minutes)
- ☐ Exchangeable ratchet head design, suitable for 9x12 mm or 14x18 mm head size
- ☐ 2 position, 52 teeth ratcheting mechanism: Forward / Reverse
- ☐ Ergonomically designed bi-component soft grip handle
- ☐ Tested and certified according to DIN EN ISO 6789, BS EN 26789, ASME B107.28



Torque Accuracy	CW $\pm 2\%$ / CCW $\pm 3\%$
Angle Accuracy	$\pm 2^\circ$ (rotating 90° at speed of $30^\circ/\text{sec}$)
Storage Memory	50 Readings
Unit Selection	Nm, Ft-Lb, In-Lb, Kg-cm, degree
Operating Mode	Peak Hold Mode / Track Mode
Head Size ■	9 x 12 mm - DT-030A2 & DT-135A3
(W x H)	14 x 18 mm - DT-200A4 & DT-340A4
Head Type	Round Head Ratchet Insert
Gear Teeth	52 Teeth
Ratcheting Mechanism	Clockwise / Counterclockwise
Working Temperature	$-10^\circ\text{C} \sim 60^\circ\text{C}$
Storage Temperature	$-20^\circ\text{C} \sim 70^\circ\text{C}$
Humidity	Up to 90% non-condensing
Battery	1.5V AA x 2pcs
Battery Life	110 Hours
Auto Shut Off	2 Minutes (when not in use)



Digital Torque / Angle Wrench with Reversible Ratchet Insert Tool



ITEM NO.	HEAD SIZE (mm)	Torque Range					Reversible Ratchet	L (mm)	
		(Nm)	(Ft-Lb)	(In-Lb)	(Kg-cm)				
DT-030A2	9 x 12	1.5~30	1.11~22.12	13.3~265.5	15.3~306.1	1/4"		390	6
DT-135A3	9 x 12	6.8~135	5.0~99.5	60~1195	69~1378	3/8"		410	6
DT-200A4	14 x 18	10~200	7.4~147.5	88~1770	102~2041	1/2"		520	6
DT-340A4	14 x 18	17~340	12.5~250.7	150~3009	173~3469	1/2"		640	6