

// Safety Wire Twisting Pliers

- ☐ Induction hardened & precision machined cutting edges
- ☐ Precision machined serrated jaws for optimum power and durability
- ☐ Automatic return action provides quick and easy wire twisting job while reduces fatigue
- ☐ Self-lock design ensures serrated jaw firmly grip wire while twisting
- ☐ Primarily used in the aviation and all forms of racing industries for wire locking nuts in safety critical applications
- ☐ Maximum wire capacity: Twist 1.0 mm dia., cut 1.0 mm (Stainless Steel)



ITEM NO.	SIZE(inch)		
DACA1A06	6	12	48
DACA1A09	9	12	48


// Reversible Safety Wire Twisting Pliers

- ☐ Induction hardened & precision machined cutting edges
- ☐ Precision machined serrated jaws for optimum power and durability
- ☐ Apply to clockwise and counterclockwise direction for wire twisting application
- ☐ Automatic return action provides quick and easy wire twisting job while reduces fatigue
- ☐ Self-lock design ensures serrated jaw firmly grip wire while twisting
- ☐ Primarily used in the aviation and all forms of racing industries for wire locking nuts in safety critical applications
- ☐ Maximum wire capacity: Twist 1.0 mm dia., cut 1.0 mm (Stainless Steel)



ITEM NO.	SIZE(inch)		
DACB1A06	6	10	40
DACB1A09	9	10	30

Step 1.



Both wire ends gripped in jaw. Lock the Pliers.

Step 2.



Pull to twist lock-wire. Push back for more travel if required.

Step 3.



Finish job with side cutter.

Step 1.



Both wire ends gripped in jaw. Lock the Pliers.

Step 2.



Pull to twist lock-wire. Push back for more travel if required.

Step 3.



Finish job with side cutter.

// Professional Series Box-Joint Water Pump Pliers with Quick-Adjust Button

- ☐ Chrome Vanadium Steel Material
- ☐ Induction hardened jaw for maximum strength and durability
- ☐ Push-lock design allows quick and easy adjustment
- ☐ With safety clamping protection to prevent injuries during application
- ☐ Accurately machined jaws provides a firm grip on cylindrical or hexagonal objects
- ☐ Fine adjustment for optimum adaptation to different size work pieces
- ☐ Comfort non-slip grip handle
- ☐ Compliance with DIN ISO 8976 specification



Gripping surfaces with special hardened teeth






Quickly adjustment by pushing a button



ITEM NO.	SIZE (inch)	GRIP CAPACITY Ø(mm)	ADJUSTMENT		
DDAG1207	7	36	18	10	40
DDAG1210	10	50	24	10	40
DDAG1212	12	66	31	10	30



BOX-JOINT WATER PUMP PLIERS WITH QUICK-ADJUST BUTTON



Fast and firm adjustment directly on the work piece