356

72

72

72

72

72

72

72

72

### Cup Type Oil Filter Wrench (For 4-Cylinder TOYOTA Engines)



Robust Aluminum Alloy Die-Castin
----------------------------------

- For 4-cylinder petrol or diesel engines from 1.8L to 2.0L Designed for quickly installation and dismantling of
- the oil filter cover during the oil filter insert Multiple contact points engaged the housing cap to grip oil filter securely
- Use with 3/8" square drive tool or 27mm wrench/socket Application: TOYOTA-Allion, Auris, Corolla Axio, Isis, Ist, Corolla Rumion, Corolla Fielder, Noah, Premio, Prius, Voxy, Wish, etc.

ITEM NO.	SIZE (mm)	FLUTES		曲
JDDH6500	64.5	14	10	40

# Cup Type Oil Filter Wrench




□JDAHA815





□JDAH7615

Automotive Cup Type Oil Filter Wrench Set



JDAH8616 JDAH9015 JDAH9210 JDAH9315 JDAHA015 100 (4") 12 15 JDAHA615 106 (4-11/64") 15 12 JDAHA815 12 108 (4-8/32") 15 JDAH6606 66 (2-19/32") 6 12 JDAH7612 76 (3") 12 12 JDAH7630 12 76 (3") 30 JDAH8618 12 86 (3-3/8") 18 JDAH9336 93 (3-21/32") 36 12 JDAH9345 93 (3-21/32") 12 45 JDAH9618 12 96 (3-3/4") 18

72 JDAHA818 108 (4-8/32") 18 12 72 74 - 76 (2-29/32" - 3") JDAH7615 72 12 75 - 77 (2-15/16 - 3-1/32") <sup>15</sup> JDAH7715 12 72

# Cup Type Oil Filter Wrench (For 4-, 6and 8-Cylinder TOYOTA Engines)



- Robust Aluminum Alloy Die-Casting
- For 4-, 6- and 8-cylinder diesel engines
- Designed for quickly installation and dismantling of the oil filter cover during the oil filter insert
- Multiple contact points engaged the housing cap to grip oil filter securely
- Use with 3/8" square drive tool or 27mm wrench/socket Application:

TOYOTA- 2007-2008 V6, Corolla-(2007-2009) 4cyl, Tundra-(2007) 8cyl, Sequoia-(2008) 8cyl, Land Cruiser-(2008-2010) 8cyl, 4Runner-(2008-2010) 4cyl, 6cyl

LEXUS- (2006)- all vehicles, (2007) ES350, GS350, GS450h, LS460, RX350, (2008) LS600h L, (2009) LX570

ITEM NO.	SIZE (mm)	FLUTES		曲
JDDH6501	64.5	14	10	40



TOPTUL cup-type oil filter wrenches are made of gauge construction and are able to withstand up to 85 ft-lbs of torque applied. The cup-design grip functions as a socket minimizing the possibility of crushing filters and fits both 3/8" and 1/2" (adapter) square drive tool. The cups are coated with electro-black oxide finish for long life protection against rust

Suitable for Japanese Vehicles

Sultable for Japanese verlicles				
ITEM NO.	CONTENTS	∰ 6 (SET)		
JGAI1401	1 64mm (2-1/2") - 14 Flutes-1 Step			
	1 65mm (2-9/16") - 14 Flutes-1 Step			
	1 68mm (2-11/16") - 14 Flutes-1 Step			
	1 73mm (2-7/8") - 14 Flutes-1 Step			
	1 74mm (2-29/32") - 15 Flutes-1 Step			
	1 74 - 76mm (2-29/32 - 3") - 15 Flutes-2 Step			
	1 76mm (3") - 30 Flutes-1 Step			
	1 75 - 77mm (2-15/16 - 3-1/32") - 15 Flutes-2 Step			
	1 80mm (3-9/64") - 15 Flutes	-1 Step		
	1 90mm (3-17/32") - 15 Flutes-1 Step			
	1 93mm (3-21/32") - 15 Flutes-1 Step			
	1 93mm (3-21/32") - 36 Flutes-1 Step			
	1 100mm (4") - 15 Flutes-1 S	tep		
	1 Adapter - 1/2"(F) x 3/8"(M)	Drive		

BLOW CASE: W415x D264 x H81 (mm)

# **// 16PCS**

TYPE

Automotive Cup Type Oil Filter Wrench Set



Suitable fo	or European Vehicles			
ITEM NO.	CONTENTS			
JGAI1601	1 66mm (2-19/32") - 6 Flu	ites-1 Step		
	1 74 - 76mm (2-29/32" - 3") - 15 Flutes-2 Ste			
	1 76mm (3") - 8 Flutes-1 Step			
	1 76mm (3") - 12 Flutes-1 Step			
	1 76mm (3") - 14 Flutes-1 Step			
	1 86mm (3-3/8") - 16 Flute	es-1 Step		
	1 86mm (3-3/8") - 18 Flute	es-1 Step		
	1 92mm (3-40/64") - 10 F	lutes-1 Step		
	1 93mm (3-21/32") - 15 F	lutes-1 Step		
	1 93mm (3-21/32") - 45 F	lutes-1 Step		
	1 96mm (3-3/4") - 18 Flute	es-1 Step		
	1 106mm (4-11/64") - 15 I	Flutes-1 Step		
	1 108mm (4-8/32") - 15 F	lutes-1 Step		
	1 108mm (4-8/32") - 18 F	lutes-1 Step		
	<ul><li>3-Legged Oil Filter Wree</li><li>65 to 120mm (2-1/2" -</li></ul>			
	1 Adapter - 1/2"(F) x 3/8"(	(M) Drive		

**BLOW CASE:** W446 x D318 x H90 (mm)