



// Heavy Duty Measuring Tape

- ☐ High impact resistant ABS case with soft grip
- ☐ Nylon coated steel tape for maximum corrosion protection & wear resistance
- ☐ Shock-Absorbing blade return bumper
- ☐ Double locking system, pause button allows blade to be stopped in any position



- ☐ Self-aligning end hook for very accurate internal/external measurements
- ☐ Decimal in red marking
- ☐ Dual scale reading in both Metric and Imperial
- ☐ Precision Class II





ITEM NO.	SIZE	TAPE WIDTH		
IAAC1903	3M/10FT	3/4" (19mm)	6	48
IAAC1905	5M/16FT	3/4" (19mm)	6	48
IAAC2508	8M/26FT	1" (25mm)	6	48
IAAC3010	10M/33FT	1-3/16" (30mm)	3	36

// Heavy Duty Metric Measuring Tape

- ☐ High impact resistant ABS case with soft grip
- ☐ Nylon coated steel tape for maximum corrosion protection & wear resistance
- ☐ Shock-Absorbing blade return bumper
- ☐ Double locking system, pause button allows blade to be stopped in any position



- ☐ Self-aligning end hook for very accurate internal/external measurements
- ☐ Decimal in red marking
- ☐ Scale in Metric size only
- ☐ Measuring accuracy according to EC accuracy class II



ITEM NO.	SIZE	TAPE WIDTH		
IAAC1903M	3M	19mm	6	48
IAAC1905M	5M	19mm	6	48
IAAC2508M	8M	25mm	6	48

// Tool Lanyard

- ☐ Fitted with one Aluminum Alloy carabiner hook
- ☐ Locking wire with spring hook and strength webbing with an elastic inner core
- ☐ Retractable tool lanyard for securing tools when working at heights
- ☐ Applicable: Drilling derricks, wind turbines, cranes, buildings, scaffolds, bridges, telecom masts and etc.



ITEM NO.	Stretches Capacity (mm)	Max. Tool Load (kg)	Strap Width (mm)		
NAAA1705	830 - 1520	5	17	12	144

// Tool Lanyard

- ☐ Fitted with two Zinc Alloy carabiner hook
- ☐ Locking wire with spring hook and strength webbing with an elastic inner core
- ☐ Retractable tool lanyard for securing tools when working at heights
- ☐ Strength webbing tail provide retrofit attachment points for a variety of tools and equipment
- ☐ 360° swivel hook prevents tangles and increases working efficiency
- ☐ Applicable: Drilling derricks, wind turbines, cranes, buildings, scaffolds, bridges, telecom masts and etc.



ITEM NO.	Stretches Capacity (mm)	Max. Tool Load (kg)	Strap Width (mm)		
NABB1705	750 - 1390	5	17	12	144